



DOME & LOW ANGLE

COMPARISON SHEET



MODULAR RINGLIGHT



SDOME II & LOW ANGLE II

| | | |
|---|------------------------------|---|
| <p>80mm OR 130mm</p> | <p>DIMENSIONS</p> | <p>80mm OR 130mm</p> |
| <p>R-C OR W-IR Red & Cyan OR White & IR</p> | <p>COLOURS</p> | <p>Red Blue Green White IR</p> |
| <p> 4 QUADRANTS</p> | <p>QUADRANTS</p> | <p>‘Not applicable’</p> |
| <p>x2.5 Brightness measured on the ring – White colour</p> | <p>BRIGHTNESS</p> | <p>x1 Brightness measured on the ring – White colour</p> |
| <p>↑ 10µs & ↓ 10µs</p> | <p>RESPONSIVENESS</p> | <p>↑ 10µs & ↓ 10µs</p> |
| <p>Continuous 50 kHz & Strobe 310 kHz</p> | <p>MAX FREQUENCY</p> | <p>‘Not applicable’</p> |
| <p>UP TO x4 </p> | <p>OVERDRIVE</p> | <p>‘Not applicable’</p> |
| <p>0V: 100% & 10V: 30%</p> | <p>DIMMING</p> | <p>‘Not applicable’</p> |
| <p>M12 5 pins & M12 8 pins</p> | <p>WIRING</p> | <p>M12 4 pins</p> |
| <p>manual & remote</p> | <p>CONTROL</p> | <p>remote</p> |
| <p> IP65</p> | <p>IP PROTECTION</p> | <p>IP30</p> |
| <p>Power & Strobe</p> | <p>LED INDICATORS</p> | <p>‘Not applicable’</p> |